


# LED ALUMINIUM PROFILES & EXTRUSIONS



DATA SHEET

LED PROFILE

**TYPE A**



## PROFILE TYPE A

	White	Black (anodized)	Inox (anodized)	Silver (anodized)	Raw
Dimensions	1000mm, 2020mm, 3000mm				
LED strip width	Up to 12mm				
Application	Surface-mounted - for decorative lighting in offices and homes				

### Covers (PVC/PMMA/PC)

Dimensions: 1000mm, 2020mm, 3000mm

Transparent	Frozen	Milky	Frosted	Milky Frosted	Lens 15	Lens 30
<b>BASIC</b>						
✦ PMMA 95%	✦ PMMA 78%	✦ PMMA 51%	✦ PMMA 90%	✦ PMMA 83%	✦ PMMA 92%	✦ PMMA 92%
✦ PVC 88%	✦ PVC 66%	✦ PVC 44%				
✦ PC 92%	✦ PC 67%	✦ PC 36%				
<b>HIGH</b>						
✦ PMMA 95%	✦ PMMA 78%	✦ PMMA 52%	✦ PMMA 87%	✦ PMMA 83%		
✦ PVC 82%	✦ PVC 65%	✦ PVC 42%				

### End caps for LED profile type A

With a hole				Without a hole			
White	Black	Inox	Silver	White	Black	Inox	Silver
<b>BASIC</b>							
<b>HIGH</b>							

### Accessories

Transparent, white, black							
Mounting clip type A MINI	Mounting clip type A	Mounting clip type A HIGH	Metal Mounting clip type A	Angled mounting clip type A	Hinges	Contactless switch	Pendants

**Maximum dissipated power of LED light sources** for temperature profile 55C: 17W with cover, 17.2W without cover. For temperature profile 65C: 22.2W with cover, 23W without cover.