


LED ALUMINIUM PROFILES & EXTRUSIONS



DATA SHEET

LED PROFILE

TYPE C










PROFILE TYPE C









| | White | Black (anodized) | Inox (anodized) | Silver (anodized) | Raw |
|-----------------|---|---|---|---|---|
| |  |  |  |  |  |
| Dimensions | 1000mm, 2020mm, 3000mm | | | | |
| LED strip width | Up to 12mm | | | | |
| Application | Angle profile 45 degrees - for lighting kitchens, stores, shelves, countertops | | | | |

Covers (PVC/PMMA/PC)







Dimensions: 1000mm, 2020mm, 3000mm

| Transparent | Frozen | Milky | Frosted | Milky Frosted | Lens 15 | Lens 30 |
|--|--|--|--|---|--|--|
| BASIC | | | | | | |
|  |  |  |  |  |  |  |
| ✦ PMMA 95% | ✦ PMMA 78% | ✦ PMMA 51% | ✦ PMMA 90% | ✦ PMMA 83% | ✦ PMMA 92% | ✦ PMMA 92% |
| ✦ PVC 88% | ✦ PVC 66% | ✦ PVC 44% | | | | |
| ✦ PC 92% | ✦ PC 67% | ✦ PC 36% | | | | |

End caps for LED profile Type C

| With a hole | | | | Without a hole | | | |
|---|---|---|---|---|--|---|---|
| White | Black | Inox | Silver | White | Black | Inox | Silver |
| BASIC | | | | | | | |
|  |  |  |  |  |  |  |  |

Accessories

| Transparent, white, black | | | | | |
|---|---|---|--|---|---|
| Mounting clip CH | Metal mounting clip CH | Angled mounting clip CH | Hinges | Contactless switch | Pendants |
|  |  |  |  |  |  |

Maximum dissipated power of LED light sources for temperature profile 55C: 16.7W with cover, 23.2W without cover. For temperature profile 65C: 23.5W with cover, 31W without cover.