


LED ALUMINIUM PROFILES & EXTRUSIONS



DATA SHEET

LED PROFILE

TYPE D















PROFILE TYPE D


	White	Black (anodized)	Inox (anodized)	Silver (anodized)	Raw
					
Dimensions	1000mm, 2020mm, 3000mm				
LED strip width	Up to 12mm				
Application	Surface-mounted profile for lighting kitchens, stores, shelves, countertops, stairs				

Covers (PVC/PMMA/PC)

Dimensions: 1000mm, 2020mm, 3000mm

Transparent	Frozen	Milky	Frosted	Milky Frosted	Lens 15	Lens 30
BASIC						
						
✧ PMMA 95%	✧ PMMA 78%	✧ PMMA 51%	✧ PMMA 90%	✧ PMMA 83%	✧ PMMA 92%	✧ PMMA 92%
✧ PVC 88%	✧ PVC 66%	✧ PVC 44%				
✧ PC 92%	✧ PC 67%	✧ PC 36%				
HIGH						
						
✧ PMMA 95%	✧ PMMA 78%	✧ PMMA 52%	✧ PMMA 87%	✧ PMMA 83%		
✧ PVC 82%	✧ PVC 65%	✧ PVC 42%				

End caps for LED profile Type D

With a hole				Without a hole			
White	Black	Inox	Silver	White	Black	Inox	Silver
BASIC							
							
HIGH							
							

Accessories

Mounting clip D MINI	Mounting clip D HIGH	Metal mounting clip D	Hinge
			

Maximum dissipated power of LED light sources for temperature profile 55C: 12W with cover, 14W without cover. For temperature profile 65C: 16W with cover, 19W without cover.