


LED ALUMINIUM PROFILES & EXTRUSIONS



DATA SHEET

LED PROFILE

TYPE G










PROFILE TYPE G





	White	Black (anodized)	Inox (anodized)	Silver (anodized)	Raw
					
Dimensions	1000mm, 2020mm, 3000mm				
LED strip width	Up to 12mm				
Application	Groove mounted profile - for lighting kitchens, stores, shelves countertops, stairs				

Covers (PVC/PMMA/PC)


Dimensions: 1000mm, 2020mm, 3000mm

Transparent	Frozen	Milky	Frosted	Milky Frosted	Lens 15	Lens 30
BASIC						
						
✦ PMMA 95%	✦ PMMA 78%	✦ PMMA 51%	✦ PMMA 90%	✦ PMMA 83%	✦ PMMA 92%	✦ PMMA 92%
✦ PVC 88%	✦ PVC 66%	✦ PVC 44%				
✦ PC 92%	✦ PC 67%	✦ PC 36%				

End caps for LED profile Type G (aluminium and plastic)

With a hole			
White	Black	Inox	Silver
BASIC			
			

Accessories



Maximum dissipated power of LED light sources for temperature profile 55C: 24.4W with cover, 25.5W without cover. For temperature profile 65C: 32.5W with cover, 34W without cover.