


# LED ALUMINIUM PROFILES & EXTRUSIONS



DATA SHEET

LED PROFILE

**TYPE H**



## PROFILE TYPE H

	White	Black (anodized)	Inox (anodized)	Silver (anodized)	Raw
Dimensions	1000mm, 2020mm, 3000mm				
LED strip width	Up to 12mm				
Application	Corner profile 30/60 degrees - for lighting kitchens, closets and stairs. Built as asymmetrical, to be used for various lighting angle				

### Covers (PVC/PMMA/PC)

Dimensions: 1000mm, 2020mm, 3000mm

Transparent	Frozen	Milky	Frosted	Milky Frosted	Lens 15	Lens 30
<b>BASIC</b>						
✦ PMMA 95%	✦ PMMA 78%	✦ PMMA 51%	✦ PMMA 90%	✦ PMMA 83%	✦ PMMA 92%	✦ PMMA 92%
✦ PVC 88%	✦ PVC 66%	✦ PVC 44%				
✦ PC 92%	✦ PC 67%	✦ PC 36%				

### End caps for LED profile Type H

<b>BASIC</b>															
With a hole								Without a hole							
White		Black		Inox		Silver		White		Black		Inox		Silver	
Left	Right	Left	Right	Left	Right	Left	Right	Left	Right	Left	Right	Left	Right	Left	Right

### Accessories

Transparent, white, black					
Mounting clip CH	Metal mounting clip CH	Angled mounting clip CH	Hinges	Contactless switch	Pendants

Maximum dissipated power of LED light sources for temperature profile 55C: 23W. For temperature profile 65C: 31W