


LED ALUMINIUM PROFILES & EXTRUSIONS



DATA SHEET

LED PROFILE

TYPE X









PROFILE TYPE X









	White	Black (anodized)	Inox (anodized)	Silver (anodized)	Raw
					
Dimensions	1000mm, 2020mm, 3000mm				
LED strip width	Up to 8mm				
Application	Surface mounted profile - for discrete lighting in kitchens, stores, countertops, handrails				

Covers (PVC/PMMA/PC)




Dimensions: 1000mm, 2020mm, 3000mm

Transparent	Frozen	Milky	Frosted	Milky Frosted	Lens 15
SLIM					
					
✦ PMMA 95% ✦ PVC 84%	✦ PMMA 79% ✦ PVC 63%	✦ PMMA 39% ✦ PVC 38%	✦ PMMA 86%	✦ PMMA 83%	✦ PMMA 96%

End caps for LED profile Type X (aluminium and plastic)

With a hole				Without a hole			
White	Black	Inox	Silver	White	Black	Inox	Silver
SLIM							
							

Accessories

Transparent, white, black / transparent		
Mounting clip X MINI	Metal mounting clip X	Hinge
		

Maximum dissipated power of LED light sources for temperature profile 55C: 14W with cover, 14.5W without cover.
For temperature profile 65C: 18W with cover, 19W without cover.