


LED ALUMINIUM PROFILES & EXTRUSIONS








DATA SHEET

LED PROFILE

TYPE Y










PROFILE TYPE Y









	White	Black (anodized)	Inox (anodized)	Silver (anodized)	Raw
					
Dimensions	1000mm, 2020mm, 3000mm				
LED strip width	Up to 12mm				
Application	Surface mounted profile - for household and office room illumination, lighting of columns, countertops				

Covers (PVC/PMMA/PC)


Dimensions: 1000mm, 2020mm, 3000mm

Transparent	Frozen	Milky	Frosted	Milky Frosted	Lens 15	Lens 30
BASIC						
						
✧ PMMA 95%	✧ PMMA 78%	✧ PMMA 51%	✧ PMMA 90%	✧ PMMA 83%	✧ PMMA 92%	✧ PMMA 92%
✧ PVC 88%	✧ PVC 66%	✧ PVC 44%				
✧ PC 92%	✧ PC 67%	✧ PC 36%				

End caps for LED profile Type Y (aluminium and plastic)

With a hole				Without a hole			
White	Black	Inox	Silver	White	Black	Inox	Silver
BASIC							
							

Accessories

Transparent, white, black / transparent					
Mounting clip Y	Metal mounting clip Y	Hinge	Assembly profile Y M1	Contactless switch	Pendants
					

Maximum dissipated power of LED light sources for temperature profile 55C: 24W with cover, 24.5W without cover.
For temperature profile 65C: 31W with cover, 31.5W without cover.