


LED ALUMINIUM PROFILES & EXTRUSIONS



DATA SHEET

LED PROFILE

TYPE Z










PROFILE TYPE Z

	White	Black (anodized)	Inox (anodized)	Silver (anodized)	Raw
					
Dimensions	1000mm, 2020mm, 3000mm				
LED strip width	Up to 12mm				
Application	Groove mounted profile - for lighting kitchens, stores, shelves and countertops				

Covers (PVC/PMMA/PC)

Dimensions: 1000mm, 2020mm, 3000mm

Transparent	Frozen	Milky	Frosted	Milky Frosted	Lens 15	Lens 30
BASIC						
						
✧ PMMA 95%	✧ PMMA 78%	✧ PMMA 51%	✧ PMMA 90%	✧ PMMA 83%	✧ PMMA 92%	✧ PMMA 92%
✧ PVC 88%	✧ PVC 66%	✧ PVC 44%				
✧ PC 92%	✧ PC 67%	✧ PC 36%				

End caps for LED profile Type Z (aluminium and plastic)

With a hole			
White	Black	Inox	Silver
BASIC			
			

Maximum dissipated power of LED light sources for temperature profile 55C: 15.8W with cover, 17W without cover.
For temperature profile 65C: 21W with cover, 22.5W without cover.